

DECLARATION OF PERFORMANCE

Nr: 960038 en

1. Unique identification code of the product-type:
Akrylfog

2. Article number:
10005057, 10005058

3. Intended use:
Sealant for non-structural use in joints in buildings for facade elements, indoors and outdoors in accordance with EN 15651-1 (F-EXT-INT)

4. Manufacturer:
ESSVE AB
Box 7091
SE 164 07 Kista
Sweden
Mail: info@essve.se

5. System of AVCP:
System 3

6. Notified body:
NB:1292 - FUNDACION TECNALIA RESEARCH & INNOVATION

7. Declared performance:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Klass E	EN 15651-1,3:2012
Release of chemicals dangerous to the environment and health	see SDS	EN 15651-1,3:2012
Water tightness and air tightness		
Resistance to flow	≤ 3mm	EN 15651-1,3:2012
Loss of volume	≤ 25%	EN 15651-1,3:2012
Adhesion/cohesion at maintained extension after water immersion (EN ISO 10590)	Pass	EN 15651-1,3:2012
Tensile properties, elongation at break at +23°C (EN ISO 8339)	≥ 25%	EN 15651-1:2012
Tensile properties at maintained	Pass	EN 15651-1, 3:2012

Essential characteristics	Performance	Harmonised technical specification
extension (EN ISO 8340)		
Adhesion/cohesion at variable temperatures (EN ISO 9047)	Pass	EN 15651-1, 3:2012
Durability	Pass	Conditioning method A / Tested on concrete M2, without primer

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Fredrik Sivertsson, Product Developer/Technical expert
Kista 2025-04-01