

## DECKING SCREW COLLATED, STAINLESS STEEL A4

### AREA OF USE

ESSVE Collated Decking Screw A4 is designed for the installation of fencing, decking timber, etc against wooden joists in very aggressive environments such as marine/offshore environments, pool areas and structures below ground level. **NOTE!** We always recommend pre-drilling for installation of hardwood decking timber, for example, Cumaru, Kirai, etc.



### DESCRIPTION

The screw is made of stainless acid proof steel, SAE316, A4. It is equipped with 1 fibre cut in the point, which minimises the risk of splintering and reduces the drive-in torque. The head is equipped with 6 cutting grooves that countersinks the screw during installation. The screw is fitted with Ph2-bit drive. ESSVE Collated Decking screw A4 are mounted on a plastic band intended for the most common autofeed screwdrivers e.g. Makita, Hilti, Senco etc.



Wood

### INSTALLATION INSTRUCTIONS

Recommended rpm: approx. 1400 - 2500/min.

### Specification

Main Materials	Stainless steel A4
Corrosion resistance class	C5 A4
Application environment	Outdoors



### Standard Pro Pack

Item no	Diameter	Length	Diameter of head	Thread length	Type of bits	Packaging	Contents	CE
601342	4,2 mm	42 mm	7,4 mm	27 mm	PH2	Cardboard box collated	1000 PCS	✓
601355	4,2 mm	55 mm	7,4 mm	27 mm	PH2	Cardboard box collated	1000 PCS	✓