

LAMINATE/PANEL SCREW, BRIGHT ZINC PLATED

AREA OF USE


ESSVE Laminate/Panel screw is specially designed for indoor installation of wall and ceiling panels. The screw has a Hi-Lo thread and can be used on wooden or steel substrate.

DESCRIPTION

The screw is produced in hardened carbon steel with bright zinc plated surface treatment. It is equipped with fibre cut at the point to reduce cracking and minimise the drive-in torque. The shape of the screw head has a low height and countersinks easily into the substrate. It is equipped with Philips crosshead Ph2. Drill capacity 0.4 – 0.9 mm. Hardened steel with bright zinc plated surface treatment. It is equipped with 1 fibre cut at the point. Equipped with crosshead Ph2.

INSTALLATION INSTRUCTIONS

Recommended rpm: 400-1200/min.



Steel



Wood

Specification

Surface treatment	Zinc plated
Main Materials	Steel
Corrosion resistance class	C1
Application environment	Indoors

C1

Standard Pro Pack

Item no	Diameter	Length	Diameter of head	Thread length	Fixture thickness	Type of bits	Drill capacity min/max	Packaging	Contents
537631	3,9 mm	30 mm	8 mm	25 mm	5 mm	PH2	0,4 - 0,9	ESSBOX 203	250 PCS
537641	3,9 mm	40 mm	8 mm	35 mm	5 mm	PH2	0,4 - 0,9	ESSBOX 203	250 PCS