

HAMMERFIXING WITH COUNTERSUNK COLLAR, PAINTED

AREA OF USE

ESSVE HF Nail Plug is designed for easier installation of battens, skirting, linings, fittings, cabinets and the like in materials such as concrete,solid brick, natural stone and hollow core slab.


DESCRIPTION

A special ribbed nail, pre-fitted in a plug. The plug has a short expansion section for solid homogeneous materials described above. The plug is manufactured of nylon.

INSTALLATION INSTRUCTIONS

For dimension 10 mm the plug and nails are supplied separated in the pack and the plug must first be pushed into the hole and then the nail is knocked in. The nail head has a Pozidriv-cross. The nail plug can then be easily removedSee the installation instructions at the end of this section.

Specification	
Surface treatment	Zinc plated
Corrosion resistance class	C1
Application environment	Indoors



Concrete



Stone



Brick

Small Pack										
Item no	Diameter	Length	Fixture thickness	Drill bit diameter	Drill depth	Anchoring depth	Type of bits	Color	Packaging	Contents
10003598	4 mm	30 mm	10 mm	4 mm	35 mm	20 mm	PZ1	Oxide	Zip-lock poly bag 7 cm	8 PCS
10003615	5 mm	35 mm	15 mm	5 mm	40 mm	20 mm	PZ2	YZP	Zip-lock poly bag 7 cm	8 PCS
10003616	5 mm	35 mm	15 mm	5 mm	40 mm	20 mm	PZ2	White	Zip-lock poly bag 7 cm	8 PCS